Platform Brief

Intel Atom® x6000E Series Processors
Intel® Pentium® N and J Series Processors
Intel® Celeron® N and J Series Processors



Driving performance, integration, and versatility with Intel's first Enhanced for IoT platform

Enhanced for IoT, Intel Atom® x6000E Series and Intel® Pentium® and Celeron® N and J Series processors deliver next-generation CPU and graphics performance with integrated support for real-time computing and Ethernet, functional safety, and industrial-centric I/Os.^{1,2}



intel.



Addressing the explosive growth of edge computing

The continued growth of computing at the edge is driving IoT devices to support more connectivity, more bandwidth, and higher levels of security—all while reducing latency. Up to 70 percent of enterprises will run varying levels of data processing at the IoT edge by 2023.³

To support the next generation of IoT edge devices, Intel has developed a new line of processors enhanced for IoT: The Intel Atom® x6000E Series and Intel® Pentium® and Intel® Celeron® N and J Series processors. These processors build on new levels of CPU and graphics performance with integrated IoT features, real-time performance, manageability, security, and functional safety.^{1,2}

Product overview

To enhance workload consolidation and meet IoT-centric requirements, Intel is introducing the Intel® Programmable Services Engine (Intel® PSE). It facilitates numerous new functions; supports real-time, ARM-based applications; and manages industrial I/Os. The integrated Intel® Safety Island supports functional safety, orchestrates Intel-on-chip diagnostics, reports errors, and monitors customer-safety applications.^{1,2}

With a choice of 12 pin-compatible options, these Intel Atom, Pentium, and Celeron processors offer a broad range of dual- or quad-core options running up to 3.0 GHz with support for both DDR4 and LPDDR4/x memory in up to 64 GB configurations. TDP ranges between 4.5W and 12W allow for implementation into a variety of design form factors with passive or active thermal solutions.

Bring next-generation graphics to the edge

These processors take a huge leap forward in graphics capabilities with Intel® UHD Graphics. Supporting eDP, DP, HDMI 2.0b, and MIPI DSI interfaces, the platform can drive a maximum resolution of 4K progressive scan at 60fps on up to three simultaneous displays, a first for this family of processors.

Integration and flexibility for IoT: The Intel® Programmable Services Engine

The Intel Programmable Services Engine (Intel PSE) is a dedicated offload engine for IoT functions powered by an ARM Cortex-M7 microcontroller. It provides independent, low-DMIPS computing and low-speed I/Os for IoT applications, plus dedicated services for real-time computing and time-sensitive synchronization.

The Intel PSE hosts new functions, including remote outof-band device management, network proxy, embedded controller lite, and sensor hub. Flexible programming, using open source code or prebuilt firmware binaries, lets you configure the Intel PSE to meet your application requirements and run real-time, ARM-based applications.

Manage devices even when the OS is unresponsive

The platform provides both remote out-of-band (OOB) and in-band (INB) device management for monitoring and remotely managing devices throughout their lifecycle. OOB management provides power control for edge devices even when the OS is unresponsive. You can restart, power down, or power up from sleep states. The INB framework facilitates over-the-air firmware and software updates while the OS is responsive. These management tools can be implemented independently of each other for your use case.

Meet strict functional safety (FuSa) requirements: Intel® Safety Island¹

Intel Atom® x6427FE and x6200FE processors meet IEC 61508 and ISO 13849 requirements (SIL2/Cat.3 PL d certified®, SIL3/Cat.4 PL e capable) for functional safety. Functional safety capabilities and highly reliable performance are built into the silicon, along with a complete set of technical documentation—safety manual, safety analysis, and user guides—which makes the customer certification process faster and simpler.

Deploy real-time computing solutions for worst-case execution-time operations and ultrareliable low-latency communication²

Intel Atom® x6000RE and Intel Atom x6000FE Series industrial processors support Intel® Time Coordinated Computing (Intel® TCC) and Time-Sensitive Networking (TSN). These technologies improve worst-case execution-time operation within individual processors and system-wide by synchronizing data, communications, and executions across networks of IoT devices.

Hardened security to help protect edge devices

Hardware-based security measures help mitigate firmware, code, and data attacks while dedicated cryptography accelerators speed up data encryption without impacting overall system performance.

Use-case possibilities

Practically any industry, sector, or application that needs higher-performance computing and graphics in a low-power design can benefit from this platform. Optional features for real-time computing and functional safety extend the platform's capabilities to critical control systems and industrial automation.

Here are a few examples:

- Real-time control systems and devices that meet functional safety requirements for industrial robots and for chemical, oil field, and energy-grid control applications
- Vehicle controls, fleet monitoring, and management systems that synchronize inputs from multiple sensors and direct actions in semiautonomous buses, trains, ships, and trucks
- Medical displays, carts, service robots, entry-level ultrasound machines, gateways, and kiosks that require AI and computer vision with reduced energy consumption
- Fixed and mobile point-of-sale (POS) systems for retail and quick-service restaurants (QSR) with high-resolution graphics
- Multifunction print/scan/copy machines that deliver rich user experiences, hardware-based data security, and remote management

Get to market faster with Intel partners and solutions

Intel is part of a large and expanding ecosystem that is driving innovation at the edge. Intel and our IoT technology partners work together to help you build and deploy high-performance, embedded devices.

Intel® IoT Solutions Alliance can help you accelerate design and deployment of intelligent devices and analytics so you can deliver first-in-market IoT solutions.

Intel® Solutions Marketplace is a searchable directory where you can find ready-to-run solutions and connect with Intel partners that can help you develop your IoT products.

Simplify development

Save time and streamline your IoT and edge AI development with our open source toolkits, production-quality software and online prototyping sandboxes.

Intel® DevCloud for the Edge gives you online access to physical clusters of the latest Intel® hardware, plus a ready-to-run installation of the Intel® Distribution of OpenVINO™ toolkit with reference implementations and pretrained module. Use it to develop and test your own computer vision applications, compare hardware performance, and choose the right platforms for your applications.

Intel® Edge Software Hub is a one-stop resource for edge computing software that provides production-quality software data and image processing, edge AI analytics, and computer vision applications.

Intel® Developer Zone for IoT brings together training materials, software tools, and development kits that can help you build, optimize, and deploy your IoT solutions.

More performance, more capabilities for IoT

improvement in SINGLE-THREAD PERFORMANCE gen over gen⁴

improvement in MULTI-THREAD PERFORMANCE gen over gen⁴

performance improvement in GRAPHICS gen over gen⁴

Integrated
FUNCTIONAL SAFETY
and REAL-TIME
COMPUTING^{1,2}

out-of-BAND and IN-BAND Remote Management

See backup for configuration details for more complete information about performance and benchmark results, visit www.intel.com/benchmarks.

4. Source: Intel. Claims based on a) SPEC CPU 2006 metric estimates based on Pre-Si projections and b) 3DMark11 estimates based on Pre-Si projections, using Intel® Pentium® J4205 as prior generation.

KEY FEATURES

Performance

- More choices for IoT: Two- and four-core options ranging from 1.0 GHz to 1.9 GHz (high-frequency mode) with burst frequencies up to 3.0 GHz
- Room for faster RAM: 4x32 LPDDR4/x @4267 MT/s, max (8 GB, 16 GB, @3200 MT/s); 2x64 DDR4 @3200 MT/s, max 32 GB
- Error correction with standard RAM: In-band errorcorrecting code (IBECC) corrects single-bit memory errors in standard, non-ECC memory
- Rich, 4K graphics: Intel UHD Graphics drives up to three independent 4Kp60 displays via DisplayPort 1.3 and HDMI 2.0b
- Improved GPU performance for AI and computer vision:
 Up to 32 execution unit (EU) cores can double as deep learning inference and computer vision engines

Hardware-based security

- Intel® Platform Trust Technology (Intel® PTT): Provides integrated TPM 2.0 capability, reducing bill of materials cost and board area.
- Intel® AES New Instructions (Intel® AES-NI), Intel® SHA
 Extensions, Intel® Secure Key: Supports hardware accelerated cryptography operations without compromising
 on productivity.
- Intel® Boot Guard: Mitigates against platform tampering using hardware root of trust.

Integrated IoT-specific services


- Dedicated ARM offload engine for IoT workloads: The Intel PSE uses an ARM microcontroller with dedicated hardware resources for real-time computing, network synchronization, and low-DMIPS computing. The Intel PSE can also host functions like out-of-band management and network proxies.
- Integrated, real-time computing: Intel TCC and TSN support worst-case execution time (WCET) and ultrareliable low-latency communication (URLLC) at the device level and across networks of devices.
- Certified⁸ for FuSa: Intel Atom x6427FE and x6200FE processors meet IEC 61508 and ISO 13849 requirements for functional safety and safety integrity levels (SIL2/Cat.3 PL d certified⁸, SIL3/Cat.4 PL e capable).
- Intel Safety Island: Integrated, functional safety IP works with the CPU to check for errors, flag and report faults, and orchestrate diagnostic tests (available on Intel Atom x6427FE and x6200FE processors).
- Remote device management: Monitor and manage devices using OOB (through wired Ethernet) capability when the OS is unresponsive and INB management (through Wi-Fi or wired Ethernet) to perform remote firmware and software updates.

Connectivity

- Integrated Ethernet: 3x 2.5GbE time-sensitive networking-enabled MACs
- High-speed lanes: Eight lanes/six ports PCIe 3.0, up to four USB 3.1 ports, and 10 USB 2.0 ports

Reference platform

Intel Atom x6000E Series and Intel Pentium and Intel Celeron N and J Series Processors⁵



PLATFORM LINEUP

Processor	Cores	Cache	CPU High- Frequency Mode	CPU Burst (Turbo) Mode	Graphics High- Frequency Mode	Graphics Burst (Turbo) Mode	Max TDP	In-Band ECC	Intel® Time Coordinated Computing	Intel® Safety Island	Package
Intel® Celeron® Processor J6413	4	1.5 MB	1.8 GHz	3.0 GHz	400 MHz	800 MHz	10W	No	No	No	FCBGA1493
Intel® Pentium® Processor J6425	4	1.5 MB	1.8 GHz	3.0 GHz	400 MHz	850 MHz	10W	No	No	No	FCBGA1493
Intel® Celeron® Processor N6211	2	1.5 MB	1.2 GHz	3.0 GHz	250 MHz	750 MHz	6.5W	No	No	No	FCBGA1493
Intel® Pentium® Processor N6415	4	1.5 MB	1.2 GHz	3.0 GHz	350 MHz	800 MHz	6.5W	No	No	No	FCBGA1493
Intel Atom [®] x6211E Processor	2	1.5 MB	1.2 GHz	3.0 GHz	350 MHz	750 MHZ	6W	Yes	No	No	FCBGA1493
Intel Atom [®] x6413E Processor	4	1.5 MB	1.5 GHz	3.0 GHz	500 MHz	750 MHZ	9W	Yes	No	No	FCBGA1493
Intel Atom [®] x6425E Processor	4	1.5 MB	1.8 GHz	3.0 GHz	500 MHz	750 MHZ	12W	Yes	No	No	FCBGA1493
Intel Atom [®] x6212RE Processor	2	1.5 MB	1.2 GHz	N/A	350 MHz	N/A	6W	Yes	Yes	No	FCBGA1493
Intel Atom [®] x6414RE Processor	4	1.5 MB	1.5 GHz	N/A	400 MHz	N/A	9W	Yes	Yes	No	FCBGA1493
Intel Atom [®] x6425RE Processor	4	1.5 MB	1.9 GHz	N/A	400 MHz	N/A	12W	Yes	Yes	No	FCBGA1493
Intel Atom [®] x6427FE Processor	4	1.5 MB	1.9 GHz	N/A	400 MHz	N/A	12W	Yes	Yes	Yes	FCBGA1493
Intel Atom [®] x6200FE Processor	2	1.5 MB	1.0 GHz	N/A	N/A	N/A	4.5W	Yes	Yes	Yes	FCBGA1493

SOFTWARE OVERVIEW

Enhanced for IoT, Intel Atom® x6000E Series and Intel® Pentium® and Celeron® N and J Series Processors support these operating systems, bootloaders, and SDKs.6

Category	Operating systems, boot loaders, and SDKs	Implementation	Distribution and Support		
	Windows 10 IoT Enterprise (64-bit)	Intel	Intel, Microsoft		
	Yocto Project BSP tool-based embedded Linux distribution (64-bit)	Intel	Intel, Yocto Project community, ISV partners		
Operating Systems⁴	Linux Ubuntu (64-bit)	Canonical Ltd.	Canonical Ltd.		
	Wind River Linux LTS distribution (64-bit)	Wind River	Wind River		
	Android 10 (64-bit) ⁷	Intel	ISV partners		
	UEFI/BIOS	IBVs	IBVs		
Boot firmware	Intel® Slim Bootloader	Intel	Bootloader ecosystem and open source community		
	coreboot	Intel	Bootloader ecosystem and open source community		
Intel® Programmable Services Engine	Intel® Programmable Services Engine firmware (Zephyr RTOS–based)	Intel	Zephyr RTOS ecosystem and open source community		
	Intel® Media SDK	Intel	Intel		
	Intel® Distribution of OpenVINO™ toolkit	Intel	Intel		
SDK	Intel® System Studio	Intel	Intel		
	Intel® Context Sensing SDK	Intel	Intel		
	Intel® Time Coordinated Computing and time-sensitive networking software toolkit	Intel	Intel		



To learn more, visit intel.com/content/www/us/en/design/products-and-solutions/processors-and-chipsets/elkhart-lake/overview.html.

- 1. Not all SKUs include the Intel® Safety Island or support functional safety.
- $2. \ \ Not all \ SKUs \ support \ real-time \ computing, time-sensitive \ computing, or \ time-synchronous \ networking.$
- ${\bf 3. \ \ Source: IDC\ Future Scape, Worldwide\ Internet\ of\ Things\ 2020\ Predictions.}$
- Source: Intel. Claims based on a) SPEC CPU 2006 metric estimates based on Pre-Si projections and b) 3DMark11 estimates based on Pre-Si projections, using Intel® Pentium® J4205 as prior generation.
 Configurations:

Performance results are based on projections as of September 1, 2020 Processor: Intel® Pentium® J6425 PL1=10W TDP, 4C4T Turbo up to 3.0 GHz Graphics: Intel Graphics Gen 11 gfx

Memory: 16GB LPDDR4-3200 OS: Windows 10 Pro Compiler version: IC18

Processor: Intel® Pentium® J4205 PL1=10W TDP, 4C4T Turbo up to 2.6 GHz

Graphics: Intel Graphics Gen 9 gfx Memory: 16GB LPDDR4-2400 OS: Windows 10 Pro Compiler version: IC18

Performance numbers are Pre-Si projections and are subject to change. Results reported may need to be revised as additional testing is conducted. The results depend on the specific platform configurations and workloads utilized in the testing, and may not be applicable to any particular users components, computer system or workloads. The results are not necessarily representative of other benchmarks.

- 5. Not all SKUs include every feature.
- 6. Not all features are supported in every operating system.
- 7. Android 10 (64-bit) availability to be determined.
- 8. Certification in process.

Notices and disclaimers

Statements in this document that refer to future plans or expectations are forward-looking statements. These statements are based on current expectations and involve many risks and uncertainties that could cause actual results to differ materially from those expressed or implied in such statements. For more information on the factors that could cause actual results to differ materially, see our most recent earnings release and SEC filings at www.intc.com.

Software and workloads used in performance tests may have been optimized for performance only on Intel microprocessors.

Performance tests, such as SYSmark and MobileMark, are measured using specific computer systems, components, software, operations, and functions. Any change to any of those factors may cause the results to vary. You should consult other information and performance tests to assist you in fully evaluating your contemplated purchases, including the performance of that product when combined with other products. For more complete information, visit www.intel.com/benchmarks.

Performance results are based on testing as of dates shown in configurations and may not reflect all publicly available updates. See backup for configuration details. No product or component can be absolutely secure.

 $SPEC^*, SPEC rate^* and SPEC \ CPU^* are registered trademarks of the Standard Performance Evaluation Corporation. See \ http://www.spec.org/spec/trademarks.html for more information.$

Results that are based on systems and components as well as results that have been estimated or simulated using an Intel Reference Platform (an internal example new system), internal Intel analysis or architecture simulation or modeling are provided to you for informational purposes only. Results may vary based on future changes to any systems, components, specifications or configurations.

Customer is solely responsible for any and all integration tasks, functions, and performance in connection with use of the Intel Products as part of a larger system. Intel does not have sufficient knowledge of any adjoining, connecting, or component parts used with or possibly impacted by the Intel Products or information about operating conditions or operating environments in which the Intel Products may be used by Customer. Intel bears no responsibility, liability, or fault for any integration issues associated with the inclusion of the Intel Products into a system. To the extent Customer utilizes Intel Products in applications related to functional safety, it is Customer's responsibility to design, manage, and assure safeguards to anticipate, monitor, and control component, system, quality, and or safety failures. Customer is solely responsible for compliance with all applicable regulatory standards and safety-related requirements concerning Customer's use of the Intel Products.

Not all features are available on all SKUs. Not all features are supported in every operating system.

Intel may change availability of products and support at any time without notice. All product plans are subject to change without notice.

Your costs and results may vary.

You may not use or facilitate the use of this document in connection with any infringement or other legal analysis concerning Intel products described herein. You agree to grant Intel a non-exclusive, royalty-free license to any patent claim thereafter drafted which includes subject matter disclosed herein.

© Intel Corporation. Intel, the Intel logo, and other Intel marks are trademarks of Intel Corporation or its subsidiaries. Other names and brands may be claimed as the property of others

1220/BC/CMD/PDF